

# RED-Health Test Report

**Client Name** : EcoFlow Inc.

**Client Address** : Plant A202, Founder Technology Industrial  
Park, Shiyan Sub-district, Bao'an District  
Shenzhen, Guangdong 518000 China

**Product Name** : Portable Power Station

**Report Date** : Oct. 14, 2022

**Shenzhen Anbotech Compliance Laboratory Limited**



# Contents

1. General Information .....	5
1.1. Client Information .....	5
1.2. Description of Device (EUT) .....	5
1.3. Auxiliary Equipment Used during Test .....	6
1.4. Description of Test Facility .....	6
2. General Product Information .....	7
2.1 Basic Restriction .....	7
2.2 Table for Filed Antenna .....	7
3. Test Result .....	8
3.1 Limit .....	8
3.2 Detailed results .....	9



## TEST REPORT

Applicant : EcoFlow Inc.

Manufacturer : EcoFlow Inc.

Product Name : Portable Power Station

Model No. : EFR600

Trade Mark :



EcoFlow

Rating(s) : Please refer to page 6

Test Standard(s) : EN IEC 62311: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the EN IEC 62311: 2020 requirements. All measurements contained in this report were conducted with the test standard listed above.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Aug. 11, 2022

Date of Test

Aug. 11~22, 2022

Prepared By

Nian xiu Chen

(Nianxiu Chen)

Approved &amp; Authorized Signer

Kingkong Jin

(Kingkong Jin)





## Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Oct. 14, 2022




## 1. General Information

### 1.1. Client Information

Applicant	:	EcoFlow Inc.
Address	:	Plant A202, Founder Technology Industrial Park, Shiyan Sub-district, Bao'an District Shenzhen, Guangdong 518000 China
Manufacturer	:	EcoFlow Inc.
Address	:	Plant A202, Founder Technology Industrial Park, Shiyan Sub-district, Bao'an District Shenzhen, Guangdong 518000 China

### 1.2. Description of Device (EUT)

Product Name	:	Portable Power Station
Model No.	:	EFR600
Trade Mark	:	 <b>ECOFLOW</b>
Test Power Supply	:	Voltage of EUT: DC 12.8V Output to RF Module: DC 3.3V
Test Sample No.	:	1-2-2(Engineering Sample)
Adapter	:	N/A
<b>WiFi</b>		
Operation Band	:	<input checked="" type="checkbox"/> 2.4GHz band <input type="checkbox"/> 5GHz band
Operation Mode	:	<input type="checkbox"/> a <input checked="" type="checkbox"/> b <input checked="" type="checkbox"/> g <input checked="" type="checkbox"/> n(HT20)
	:	<input checked="" type="checkbox"/> n(HT40) <input type="checkbox"/> ac(VHT20) <input type="checkbox"/> ac(VHT40) <input type="checkbox"/> ac(VHT80)
	:	<input type="checkbox"/> ac(VHT160) <input type="checkbox"/> ax(HEW20) <input type="checkbox"/> ax(HEW40) <input type="checkbox"/> ax(HEW80)
	:	<input type="checkbox"/> ax(HEW160)
Modulation Type	:	<input type="checkbox"/> 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)
	:	<input checked="" type="checkbox"/> 802.11b: DSSS (CCK, DQPSK, DBPSK)
	:	<input checked="" type="checkbox"/> 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM)
	:	<input checked="" type="checkbox"/> 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
	:	<input type="checkbox"/> 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
	:	<input type="checkbox"/> 802.11ax: OFDMA(BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
<b>Bluetooth</b>		
Operation Mode	:	<input type="checkbox"/> BT BDR <input type="checkbox"/> BT EDR <input checked="" type="checkbox"/> BLE 1M <input checked="" type="checkbox"/> BLE 2M
Modulation Type	:	<input checked="" type="checkbox"/> GFSK <input type="checkbox"/> $\pi/4$ -DQPSK <input type="checkbox"/> 8-DPSK
<b>Remark:</b> 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		



### 1.3. Auxiliary Equipment Used during Test

Description	Rating(s)
--	--

### 1.4. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

#### ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

#### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518128

#### Rating(s):

<b>Portable Power Station/station électronique portable</b>	
<b>Model/Modèle:</b>	EFR600
<b>Capacity/Capacité:</b>	256Wh (20Ah 12.8V $\overline{\text{---}}$ )
<b>Discharge Temperature/Température d'utilisation:</b>	-10 to 45°C (14 to 113°F)
<b>Charge Temperature/Température de recharge:</b>	0 to 45°C (32 to 113°F)
<b>AC Input/entrée:</b>	200-240V~ 50Hz/60Hz 8A Max
<b>Solar/Solaire/DC Input/entrée:</b>	11-30V $\overline{\text{---}}$ 8A 110W Max
<b>Total Output/sortie totale:</b>	484W
<b>DC Output/sortie:</b>	12.6V $\overline{\text{---}}$ 8A 100W Max
<b>AC Output/sortie(x1):</b>	230V~1.3A (total) 50Hz/60Hz 300W
<b>AC Output/sortie/(Bypass/Dérivation)(x1):</b>	200-240V~ 600W (total) 50Hz/60Hz
<b>USB-A Output/sortie(x2):</b>	5V $\overline{\text{---}}$ 2.4A 12W Max per port
<b>USB-C Input/Output/entrée/sortie(x1):</b>	5/9/12/15/20V $\overline{\text{---}}$ 3A 60W Max





## 2. General Product Information

### 2.1 Basic Restriction

The essential requirements of Directive 99/519/EC in the article 3.1(a) and the limits must be taken from Council Recommendation 99/519/EC for General Population or from the ICNIRP Guidelines for Occupational Exposure. EN 50371:2002 Generic standard to demonstrate the compliance of low power electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields. The average power of EUT is less than 20mW then comply with basic restriction (1999/519/EC) without test.

### 2.2 Table for Filed Antenna

Specification	Antenna Type	Gain (dBi)
BLE	PCB Antenna	3.96
WiFi 2.4G	PCB Antenna	3.96



### 3. Test Result

#### 3.1 Limit

##### Council Recommendation 99/519/EC Annex III

Reference levels for electric, magnetic and electromagnetic fields (0Hz to 300GHz)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density Seq (W/m <sup>2</sup> )
0-1Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8Hz	1000	$3,2 \times 10^4 / f^2$	$4 \times 10^4 / f^2$	-
8-25Hz	1000	$4000 / f$	$5000 / f$	-
0.025Hz-0,8kHz	$250 / f$	$4 / f$	$5 / f_{6,25}$	-
0,8-3kHz	$250 / f$	5	6,25	-
3-150kHz	87	5	6,25	-
0,15-1MHz	87	$0.73 / f$	$0.92 / f$	-
1-10MHz	$87 / f^{1/2}$	$0.73 / f$	$0.92 / f$	-
10-400MHz	28	0.073	0,092	2
400-2000MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f / 200$
2-300GHz	61	0,16	0,20	10

Note:

(1)As indicated in the frequency range column.

(2)For frequencies between 100kHz and 10GHz, Seq, E2, H2 and B2 are to be averaged over any six-minute period.

(3)For frequencies exceeding 10GHz, Seq, E2, H2 and B2 are to be averaged over any 68/1.05-minute period (.in GHz).

(4)No E-field value is provided for frequencies <1Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 20kV/m. Spark discharges causing stress or annoyance should be avoided.





### 3.2 Detailed results

#### 3.2.1 MPE Evaluation

$$S = PG * \text{Duty factor} / 4\pi R^2$$

P = Peak Power Input to antenna (Watts)

G =Antenna Gain (numeric)

R = distance to the center of radiation of antenna (in meter) = 0.20 m

Note:

1)  $P \text{ (Watts)} = (10^{(\text{dBm} / 10)}) / 1000$

2)  $G \text{ (Antenna gain in numeric)} = 10^{(\text{Antenna gain in dBi} / 10)}$

3) Duty factor=1

4)  $\pi = 3.142$

The maximum power density at a distance of 0.2 m for EUT is shown as below:

Test Mode	Antenna Gain(dBi)	Peak Output Power (dBm)	Peak Output Power (W)	Duty factor	Calculated RF Exposure (W/ m <sup>2</sup> )	Limit (W/ m <sup>2</sup> )
BLE	3.96	4.71	0.0030	1.0000	0.0146	10
WiFi 2.4G	3.96	16.54	0.0451	1.0000	0.2232	10

----- End of Report -----

